


Standard Impulse Wrench – RRI-S / RRI-R series



Img.: RRI-60S



Img.: RRI-30SA



Series RRI-S


| Type | Model | | Item No. | Bolt Capacity Ø | RPM min ⁻¹ | Torque Range* N-m | Air Cons. l/s | Weight kg | Pipe Thread Inch | Hose ID mm | Dimensions | | Vibration m/s ² | Noise Level dB(A) | |
|----------|-------|-----|-----------|--------------------|--------------------------|----------------------|------------------|--------------|---------------------|---------------|------------|------|-------------------------------|----------------------|----|
| | SqD | Hex | | | | | | | | | A | B | | | |
| Straight | - | 1/4 | RRI-30 SA | 510505 | M6 | 4200 | 6 - 11,5 | 3,7 | 0,77 | 1/4 | 6,5 | 219 | n.a. | 2,7 | 78 |
| | - | 1/4 | RRI-40 SA | 510515 | M6-M8 | 4200 | 10 - 17 | 3,7 | 0,8 | 1/4 | 6,5 | 224 | n.a. | 3,1 | 78 |
| | - | 1/4 | RRI-50 SA | 510525 | M8 | 6800 | 15 - 25 | 5,3 | 0,8 | 1/4 | 6,5 | 224 | n.a. | 3,4 | 80 |
| | - | 1/4 | RRI-60 SA | 510235 | M8 | 6000 | 20 - 30 | 6,2 | 0,86 | 1/4 | 8 | 225 | n.a. | 3,8 | 80 |
| | - | 1/4 | RRI-70 SA | 510545 | M8-M10 | 5000 | 28 - 40 | 6,2 | 0,97 | 1/4 | 8 | n.a. | n.a. | n.a. | 80 |
| | 3/8 | - | RRI-30 S | 510510 | M6 | 4200 | 7 - 12,5 | 3,7 | 0,8 | 1/4 | 6,5 | 219 | n.a. | 2,6 | 78 |
| | 3/8 | - | RRI-40 S | 510520 | M6-M8 | 4200 | 11 - 19 | 3,7 | 0,8 | 1/4 | 6,5 | 221 | n.a. | 2,9 | 78 |
| | 3/8 | - | RRI-50 S | 510530 | M8 | 6800 | 16 - 27 | 5,3 | 0,8 | 1/4 | 6,5 | 221 | n.a. | 3 | 80 |
| | 3/8 | - | RRI-60 S | 510540 | M8-M10 | 6000 | 22 - 35 | 6,2 | 0,86 | 1/4 | 8 | 231 | n.a. | 3,4 | 80 |
| | 3/8 | - | RRI-70 S | 510550 | M10 | 5000 | 31 - 47 | 6,2 | 0,97 | 1/4 | 8 | 244 | n.a. | 3,7 | 80 |



Img.: RRI-70R



Img.: RRI-50RA



Series RRI-R

| Type | Model | | Item No. | Bolt Capacity Ø | RPM min ⁻¹ | Torque Range* N-m | Air Cons. l/s | Weight kg | Pipe Thread Inch | Hose ID mm | Dimensions | | Vibration m/s ² | Noise Level dB(A) | |
|--------|-------|-----|-----------|--------------------|--------------------------|----------------------|------------------|--------------|---------------------|---------------|------------|-----|-------------------------------|----------------------|----|
| | SqD | Hex | | | | | | | | | A | B | | | |
| Angled | - | 1/4 | RRI-50 RA | 510605 | M6-M8 | 4300 | 9,5 - 16 | 4,8 | 1,2 | 1/4 | 6,5 | 253 | n.a. | 16,5 | 80 |
| | - | 1/4 | RRI-60 RA | 510615 | M8 | 4700 | 15 - 22 | 6,2 | 1,3 | 1/4 | 8 | 264 | n.a. | 17,2 | 80 |
| | - | 1/4 | RRI-70 RA | 510625 | M8 | 4500 | 20 - 29 | 6,2 | 1,4 | 1/4 | 8 | 272 | n.a. | 17,5 | 80 |
| | 3/8 | - | RRI-50 R | 510610 | M6-M8 | 4300 | 10,5 - 17 | 4,8 | 1,2 | 1/4 | 6,5 | 253 | n.a. | 16 | 80 |
| | 3/8 | - | RRI-60 R | 510620 | M8 | 4700 | 16 - 24 | 6,2 | 1,3 | 1/4 | 8 | 264 | n.a. | 16,8 | 80 |
| | 3/8 | - | RRI-70 R | 510630 | M8-M10 | 4500 | 22 - 31 | 6,2 | 1,4 | 1/4 | 8 | 272 | n.a. | 17,1 | 80 |
| | 1/2 | - | RRI-70 RG | 510631 | M10 | 2000 | 32 - 45 | 6,2 | 1,6 | 1/4 | 8 | 281 | n.a. | 17,4 | 82 |
| | 1/2 | - | RRI-70 RH | 510632 | M10-M12 | 2200 | 46 - 60 | 6,2 | 1,6 | 1/4 | 8 | 281 | n.a. | 17,4 | 82 |



Further information available 24 / 7 on our website.

* Torque specification is for guidance only, based on manufacturer's tightening tests at 0.6 MPa. Due to different influencing factors, practical values may deviate.