


Standard Shut-Off Impulse Wrench – RRI-ST / RRI-RT series



Img.: RRI-60ST



Img.: RRI-30STA



Series RRI-ST


Type	Model		Item No.	Bolt Capacity Ø	RPM min ⁻¹	Torque Range* N-m	Air Cons. l/s	Weight kg	Pipe Thread Inch	Hose ID mm	Dimensions		Vibration m/s ²	Noise Level dB(A)	
	Sqd	Hex									A	B			
Straight	-	1/4	RRI-30 STA	510105	M6	4200	6 - 11,5	3,7	0,77	1/4	6,5	219	n.a.	2,7	78
	-	1/4	RRI-40 STA	510115	M6-M8	4200	10 - 17	3,7	0,8	1/4	6,5	224	n.a.	3,1	78
	-	1/4	RRI-50 STA	510125	M8	6800	15 - 25	5,3	0,8	1/4	6,5	224	n.a.	3,4	80
	-	1/4	RRI-60 STA	510135	M8	6000	20 - 30	6,2	0,86	1/4	8	225	n.a.	3,8	80
	-	1/4	RRI-70 STA	510145	M8-M10	5000	28 - 40	6,2	0,97	1/4	8	n.a.	n.a.	n.a.	80
	3/8	-	RRI-30ST	510110	M6	4200	7 - 12,5	3,7	0,8	1/4	6,5	219	n.a.	2,6	78
	3/8	-	RRI-40ST	510120	M6-M8	4200	11 - 19	3,7	0,8	1/4	6,5	221	n.a.	2,9	78
	3/8	-	RRI-50ST	510130	M8	6800	16 - 27	5,3	0,8	1/4	6,5	221	n.a.	3	80
	3/8	-	RRI-60ST	510140	M8-M10	6000	22 - 35	6,2	0,86	1/4	8	231	n.a.	3,4	80
	3/8	-	RRI-70ST	510150	M10	5000	31 - 47	6,2	0,97	1/4	8	244	n.a.	3,7	80
	3/8	-	RRI-80ST	510160	M10-M12	6100	40 - 68	n.a.	1,15	1/4	8	248	n.a.	4	82



Img.: RRI-70RT



Img.: RRI-50RTA



Series RRI-RT

Type	Model		Item No.	Bolt Capacity Ø	RPM min ⁻¹	Torque Range* N-m	Air Cons. l/s	Weight kg	Pipe Thread Inch	Hose ID mm	Dimensions		Vibration m/s ²	Noise Level dB(A)	
	Sqd	Hex									A	B			
Angled	-	1/4	RRI-50RTA	510205	M6-M8	4300	9,5 - 16	4,8	1,2	1/4	6,5	253	n.a.	16,5	80
	-	1/4	RRI-60RTA	510215	M8	4700	15 - 22	6,2	1,3	1/4	8	264	n.a.	17,2	80
	-	1/4	RRI-70RTA	510225	M8	4500	20 - 29	6,2	1,4	1/4	8	272	n.a.	17,5	80
	3/8	-	RRI-50RT	510210	M6-M8	4300	10,5 - 17	4,8	1,2	1/4	6,5	253	n.a.	16	80
	3/8	-	RRI-60RT	510220	M8	4700	16 - 24	6,2	1,3	1/4	8	264	n.a.	16,8	80
	3/8	-	RRI-70RT	510230	M8-M10	4500	22 - 31	6,2	1,4	1/4	8	272	n.a.	17,1	80
	1/2	-	RRI-70RGT	510231	M10	2000	32 - 45	6,2	1,6	1/4	8	281	n.a.	17,4	82
	1/2	-	RRI-70RHT	510232	M10-M12	2200	46 - 60	6,2	1,6	1/4	8	281	n.a.	17,4	82
	1/2	-	RRI-80RHT	510242	M12	2800	50 - 70	n.a.	1,7	1/4	8	281	n.a.	19	82



Further information available 24 / 7 on our website.

* Torque specification is for guidance only, based on manufacturer's tightening tests at 0.6 MPa. Due to different influencing factors, practical values may deviate.