







## **Battery Impulse Wrench** – YZ-NP series



- Power output via Yokota Twin-Blade hydraulic pulse unit, driven by battery powered brushless DC electric motor.
- ► Li-ion battery 18 V / 2.0 Ah:
  - No memory effect
  - Battery securely locked
  - Capacity control LED
- ▶ 4 rpm settings: 2000/3000/4000/4800 rpm, to be set according to application/ joint conditions.
- Error LED indication:
  - Overheat error
  - Motor/driver error
  - Battery low
- Compact design:
  - No planet gear between motor and impulse unit
  - Light weight

**YZ-NP** series

3/8

- Very well balanced
- One-hand operation.
- ► Low vibration, low noise.

Yokota YZ-NP battery impulse wrenches are powerful, very accurate and most important, have no kick-back. The very compact design offers great accessibility to the joint.

Tightening bolts M6 up to M10 with torque levels up to 60 Nm with very high speed and remarkably low reaction forces.

The combination of adjustment of the relief valve and speed setting of the motor gives a great fit-for-purpose adaptation to the specific bolted joint.

Battery (BPL-1820) and Charger (BC0075MX) have to be ordered separately.

Applying reaction-free Yokota impulse wrenches at the assembly line reduces the RSI risk significantly. As a result, the number of sick notifications caused by musculoskeletal complaints is noticeably reduced and acceptance by the operator is significantly increased.

**Pulse-Check Function**: By teaching the tool the impulse cycle as a reference point, the YZ-NP is able to give a warning message for upcoming maintenance needs.

## **Scope of Supply**

- Battery impulse tool YZ-NP
- NEW: Battery pack BPL-1820 incl.
- Rubber protector (col. dep. on model)
- Adjusting pin TF
- Operating manual

## **Options, Accs & Spares**

- O Li-Ion battery BPL-1820 #430110
- O Charger BC0075MX #430115
- Rubber protection cover (pistol)
  - YZ600 #0454-0029-00-00 (white)
  - YZ800 #0455-0029-00-00 (blue)
  - YZ900 #0456-0029-00-00 (black)
  - YZ950 #0457-0029-00-00 (green)
- O Rubber protection cover (battery) #0446-0029-00-01













For impulse wrenches we recommend power sockets and extensions with sleeve drive — less tolerance, less wear for a permanently constant power output.



Type / Drive		/e	Model	Item No.	Torque Range	Bolt Capacity	Speed (4 steps)	Tightenings per charge	Dimensions mm		Weight w/o / with batt		Vibra- tion	Noise Level
	SqD	Hex			N·m		min <sup>-1</sup>	pcs	Α		kg	kg	m/s²	dB(A)
Pistol	-	1/4	YZ-NP 600A	420870	7 - 18	M6	2000 - 4800	1300	157	29.5	1.00	1.41	< 2.5	67
	-	1/4	YZ-NP 800A	420872	15 - 30	M6-M8	2000 - 4800	800	157	29.5	1.05	1.46	< 2.5	68
	3/8	-	YZ-NP 600E	420871	9 - 20	M6	2000 - 4800	1300	152	29.5	1.00	1.41	< 2.5	67
	3/8	_	YZ-NP 800E	420873	18 - 35	M6-M8	2000 - 4800	800	157	29.5	1.05	1.46	< 2.5	68

2000 - 4800

2000 - 4800

700

650

164

29.5

1.20



YZ-NP 900E

YZ-NP 950E

420874

420875

34 - 50

45 - 60

<sup>1</sup>) All data according to manufacturer (Yokota Japan). Reference values determined under test conditions (tightening time 0.5 s at ambient temperature 30°C); varies depending on actual conditions. <sup>2</sup>) Speed adjustable in 4 steps. <sup>3</sup>) Delivery now includes battery pack, therefore changed item numbers.

M8-M10

M10



1.61

1.66

< 2.5



70

70