









Battery Impulse Wrench with smart Shut-Off – YZ-T series



- ▶ Power output via hydraulic Yokota twinblade pulse unit, driven by a battery powered brushless DC electric motor.
- ► Lithium Ion battery 18 V / 2.0 Ah:
 - no memory effect
 - charging indicator.
- 3 speed levels, freely programmable.
- ► Feedback via LED:
 - OK / NG
 - LED visible from almost all around.
- Ergonomic design:
 - no planet gear between motor and impulse unit
 - low weight
 - well balanced
 - one-handed right / left reversible.
- Very low vibration, low noise level.
- Non-contact trigger and L/R reverse switch.
- ► Main Shaft with spring+pin (type E).
- Easy maintenance after extended interval.
- Parameter input via Laptop or Programming Console (PC-1-YZ-T).

urther infor-

mation availa-ble 24 / 7 on

our website.

Shipping incl. rubber protector, Li-lon battery pack, and TF pin.


The Yokota YZ-T cordless impulse wrench is detecting the amplitude of the tightening force from the motor loaded condition. Based on the programmed values, the YZ-T wrench makes self-shut-off intelligently. As a result, the YZ-T achieves highest torque accuracy and safety against misconnections.

An integrated status LED is visible virtually all around. The YZ-T series provides a rugged, impact-resistant housing. Its pulse cell works without a mechanical shut-off mechanism and is easy to maintain. The optimized design allows extended maintenance intervals. The grip fits well in the hand and the tool is perfectly balanced.

Intelligent shut-off

The combination of the adjustment of the pressure relief valve and the speed setting of the motor allows an optimal adaptation to the respective bolt joint to be connected.

Thus the electronically controlled shut-off effects precisely and stable according to the entered parameters for smallest torque tolerances.



Options, Accs & Spares

- O Li-Ion battery BPL-1820 #430110
- O Battery charger BC0075G #430115
- O Rubber protector (see YZ-NP)
- Rubber protector (battery) #0446-0029-00-01
















Progr. Console

- Edit parameters
- Show/review and analyze results
- ▶ Display OK / NG



турс	, Dilvi	
	SqD	Hex
		1//

YZ-T series

Type / Drive		Model	Item No.	Torque Range	Free Speed (rpm) min ⁻¹			Dimensions mm		Weight w Batt	Vibra- tion	Noise Level	
	SqD	Hex			N·m	Low	Middle	High	A		kg	m/s²	dB(A)
Pistol	-	1/4	YZ-T 600A	420570	5 - 18	1200-1500	1500-3000	2000-4800	161	29.5	1.41	< 2.5	67
	_	1/4	YZ-T 800A	420572	10 - 30	1200-1500	1500-3000	2000-4800	161	29.5	1.41	< 2.5	67
	3/8	-	YZ-T 600E	420571	7 - 20	1200-1500	1500-3000	2000-4800	166	29.5	1.51	< 2.5	68
	3/8	-	YZ-T 800E	420573	15 - 35	1200-1500	1500-3000	2000-4800	166	29.5	1.51	< 2.5	68
	3/8	_	YZ-T 900E	420574	30 - 50	1200-1500	1500-3000	2000-4800	173	29.5	1.61	< 2.5	69
	3/8	_	YZ-T 950E	420575	40 - 60	1200-1500	1500-3000	2000-4800	173	29.5	1.66	< 2.5	70
	3/8	_	YZ-T 980E	420576	45 - 65	1200-1500	1500-3000	2000-3000	241	34	2.21	<2.5	79
	1/2	_	YZ-T 1000E	420577	60 - 80	1200-1500	1500-3000	2000-3000	241	34	2.21	<2.5	79



Notes: 1) Models "A" equipped with 1/4" hexagonal guick change chuck; models "E" provide spring+pin in square drive shaft. 2) For impulse wrenches we recommend our extensive range of sleeve drive power sockets (p. 38 ff).

